

(N)HMH-J halogen-free for fixed installation, emission-free, 300/500V



Technical data

- Plastic-sheathed cable, halogen-free, for fixed installation
- Adapted to DIN VDE 0250 part 214
- Permissible **working temperature** at the conductor +70°C
- **Nominal voltage**
U₀/U 300/500 V
- Max. **voltage** for equipment
U_m 550 V
- **Power rating**
- **Caloric load values**
see Technical Informations

Cable construction

- Bare Cu conductor, solid or stranded on the basis of DIN VDE 0250 part 204 with the following modifications:
- Core insulation of halogen-free thermoplastic polymer compound with optimum wall thickness
- Colour coded to DIN VDE 0293-308
- Green-yellow earth core, 3 cores and above
- for 1 core cable
core colour green-yellow
- Cores stranded in layer
- Extruded core insulation, halogen-free
- Outer jacket of non-cross-linked, halogen-free thermoplastic polymer compound
- Jacket colour light-grey (RAL 7035)

Properties

- **Corrosive nature of combustion gases (halogen-free verification)**
testing acc. to DIN VDE 0482 part 267, EN 50267-2-2, IEC 60754-2, HD 602 (equivalent DIN VDE 0472 part 813)
- **Behaviour in case of fire**
testing according to DIN VDE 0482 part 265-2-1, EN 50265-2-1 and IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)
- **Low smoke**
testing acc. to DIN VDE 0472 part 818

Note

- re = round conductor, single-wire;
- rm = round conductor, multiple-wire.
- G = with green-yellow earth core.
- O-version: single core conductor with black core insulation. Cables with between two and seven cores are without green-yellow core.
- J-version: with green-yellow core insulation.
- AWG sizes are approximate equivalent values. The actual cross-section is in mm².

Application

This plastic-sheathed cable of defined behaviour in case of fire is used for installations in residential dwellings, public buildings as well as in industrial constructions.

Suitable for applications in dry, damp or wet environments for installation above, on, in and beneath plaster, as well as in masonry and concrete walls, not however for embedding in vibration, compacted or tamped concrete.

The cable is also approved for outdoor applications provided these are not exposed to direct sunlight radiation. Installation of this cable in earth or in water is not permitted.

CE = The product is conformed with the EC Low-Voltage Directive 73/23/EEC and 93/68/EEC.

Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
51996	3 G 1,5 re	9,2	43,0	92,0	16
52001	4 G 1,5 re	9,9	58,0	115,0	16
52009	5 G 1,5 re	11,0	72,0	133,0	16
52016	7 G 1,5 re	11,4	101,0	168,0	16
51997	3 G 2,5 re	10,6	72,0	128,0	14
52002	4 G 2,5 re	11,0	96,0	152,0	14
52010	5 G 2,5 re	12,0	120,0	182,0	14
52017	7 G 2,5 re	13,7	158,0	250,0	14
51992	1 G 4 re	9,5	38,0	62,0	12
51998	3 G 4 re	12,0	115,0	192,0	12
52003	4 G 4 re	13,4	154,0	244,0	12
52011	5 G 4 re	15,0	192,0	300,0	12
51993	1 G 6 re	10,0	58,0	83,0	10
51999	3 G 6 re	13,5	173,0	267,0	10
52004	4 G 6 re	15,9	230,0	345,0	10
52012	5 G 6 re	15,9	288,0	400,0	10
51994	1 G 10 re	11,5	96,0	125,0	8
52000	3 G 10 re	15,9	288,0	628,0	8

Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
52005	4 G 10 re	17,5	384,0	522,0	8
52013	5 G 10 re	19,0	480,0	620,0	8
51995	1 G 16 rm	12,9	154,0	188,0	6
52006	4 G 16 rm	19,9	614,0	815,0	6
52014	5 G 16 rm	24,4	768,0	995,0	6
52007	4 G 25 rm	27,4	960,0	1305,0	4
52015	5 G 25 rm	29,9	1200,0	1580,0	4
52008	4 G 35 rm	30,4	1344,0	1750,0	2

Dimensions and specifications may be changed without prior notice.